



P.O. Box 14300, Washington, DC 20044-4300 • p202 624-2500 • f202 628-8844
Courier Address: 1001 Pennsylvania Avenue, NW, Washington, DC 20004-2595

FACSIMILE COVER PAGE

Date: December 21, 2004

To: Examiner CANTELMO

**RECEIVED
CENTRAL FAX CENTER**

Firm: USPTO

DEC 21 2004

Facsimile Telephone Number: (703) 872-9306

Total Number of Pages (Includes Cover Sheet): 6

From: Christopher T. McWhinney

Phone: (571) 272-1283

CAM Number: 080449.50806US

User ID: 1408

Message: Re: *Application No. 10/019,488*

Please see the attached proposed claim amendments.

Thank you.

--Christopher T. McWhinney

This message is intended only for the use of the individual to whom, or entity to which, it is addressed and may contain information that is privileged, confidential, and exempt from disclosure under applicable law.

If the reader of this message is not the intended recipient or the employee or agent responsible for delivering this message to the intended recipient, you are hereby notified that any dissemination, distribution, or copying of this communication is prohibited. If you have received this communication in error, please notify us immediately by telephone (collect), and return the original message to us at the address listed above via the U.S. Postal Service.

Thank You.

Hard Copy to Follow:

☐ Yes ☒ No

PROPOSED AMENDMENT

1 - 13. (Canceled)

14. (Currently Amended) A gastight cell for the storage of electrochemical energy, comprising at least one positive nickel oxide electrode and at least one hydrogen-storing negative electrode, a hydrophilic separator being arranged between the positive and negative electrodes, with n positive electrodes and (n+1) negative electrodes, the two outmost electrodes being negative electrodes, which are each flanked by one transport element, and an alkaline electrolyte or an alkaline electrolyte mixture, wherein one or more negative electrodes are provided with a gas-permeable, hydrophobic transport element for transporting the gases of the cell atmosphere, and wherein all of the negative electrodes are hydrogen-storing negative electrodes.

15. (cancelled)

16. (Currently Amended) A gastight cell for the storage of electrochemical energy, comprising at least one positive nickel oxide electrode and at least one hydrogen-storing negative electrode, a hydrophilic separator being arranged between the positive and negative electrodes, and an alkaline electrolyte or an alkaline electrolyte mixture, wherein one or more negative electrodes are

provided with a gas-permeable, hydrophobic transport element for transporting the gases of the cell atmosphere, and wherein all of the negative electrodes are hydrogen-storing negative electrodes. ~~The cell as claimed in claim 14,~~ wherein the negative electrodes comprise split electrodes and unsplit electrodes, the split electrodes comprising one or more negative electrodes that are split into two parts, the two parts being separated from one another by a hydrophobic, gas-permeable transport element.

17. (Previously Presented) The cell as claimed in claim 16, comprising a plurality of positive and negative electrodes that are alternately arranged, wherein every second negative electrode is split into two parts.

18. (Previously Presented) The cell as claimed in claim 16, wherein the two parts of the split negative electrodes each have half the thickness or half the capacitance of one of the unsplit negative electrodes in the cell.

19. (Previously Presented) The cell as claimed in claim 14, wherein the transport element is a hydrophobic nonwoven layer.

20. (Previously Presented) The cell as claimed in claim 19, wherein the hydrophobic nonwoven layer comprises electrolyte-repelling polypropylene fibers.

21. (Previously Presented) The cell as claimed in claim 14, wherein the positive electrodes are fibrous-structure framework electrodes.

22. (Previously Presented) The cell as claimed in claim 14, wherein the separator comprises nonwoven polyamide fiber or hydrophilic nonwoven polypropylene fiber.

23. (Currently Amended) The cell as claimed in claim 14, wherein the at least one negative electrode comprises a metallic substrate material, to which an active compound is applied, the active compound comprising ~~being obtainable from~~ a paste which comprises a dry fraction and a liquid fraction, the dry fraction comprising a mixture of a pulverulent storage alloy for hydrogen, soot and polytetrafluoroethylene (PTFE), and the liquid fraction comprising a mixture of water and an alcohol which has 3 to 6 C atoms.

24. (Previously Presented) The cell as claimed in claim 23, wherein the dry fraction comprising particles of the storage alloy being covered with polytetrafluoroethylene in the manner of fibrils.

25. (Previously Presented) The cell as claimed in claim 23, wherein the dry fraction comprises 85 to 95 parts of the alloy for storing hydrogen, 2 to 10 parts of soot and 3 to 8 parts of PTFE.

26. (Previously Presented) The cell as claimed in claim 23, wherein the liquid fraction contains 30 to 70 parts by volume of water and 70 to 30 parts by volume of the alcohol.

27. (Previously Presented) The cell as claimed in claim 23, wherein the dry fraction further comprises 0.2% by weight of polyethylene glycol.

28. (Previously Presented) The cell as claimed in claim 23, wherein the liquid fraction comprises polyethylene glycol.

29. (Previously Presented) The cell as claimed in claim 23, wherein the dry fraction and the liquid fraction has a mass ratio of 4:1 to 6:1.

30. (Previously Presented) A gastight cell for the storage of electrochemical energy, comprising at least one positive nickel oxide electrode and at least one hydrogen-storing negative electrode, a hydrophilic separator being arranged between the positive and negative electrodes, and an alkaline electrolyte or an alkaline electrolyte mixture, wherein one or more negative electrodes are provided with a gas-permeable, hydrophobic transport element for transporting the gases of the cell atmosphere, and wherein none of the electrodes are auxiliary.

electrodes, the two outmost electrodes being negative electrodes, which are each flanked by one transport element.

31. (Currently Amended) A gastight cell for the storage of electrochemical energy, comprising:

a plurality of electrodes consisting essentially of

one or more positive nickel oxide electrodes, and

two one or more hydrogen-storing negative electrodes;

a hydrophilic separator arranged between each of the positive and negative electrodes; and

an alkaline electrolyte or an alkaline electrolyte mixture,

wherein one or more negative electrodes are provided with a gas-permeable, hydrophobic transport element for transporting the gases of the cell atmosphere, the two outmost electrodes being negative electrodes, which are each flanked by one transport element.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.